













T15 Series

Mini Terminals & Mini Earth Terminals for TS15 Rails



	ER2.5-T15 Width 5mm	ER4-T15 Width 6mm
Electrical Ratings		
Voltage / Current / Cross Section	400V~ / 24A / 2.5mm ²	400V~ / 32A / 4mm ²
VDE		
UL	300V ~ / 20A / AWG 26-12	300V ~ / 30A / AWG 26-10
ATEX	400V ~ / 23A / 2.5mm ²	400V ~ / 31.5A / 4mm ²
Connection Data		
Insulation Stripping Length / Torque	10mm / 0.4Nm	10mm / 0.5Nm
Solid Strand	0.5 - 4mm ²	0.5 - 6mm ²
Fine Strand, with Ferrule	0.5 - 2.5mm ²	0.5 - 4mm ²
AWG Conductor	26.....12	26.....10
End Bracket		
Thickness 8mm	 ES5	ES5
End Plate		
Polyamide 66 - Thickness 3mm	 EP1.5-4	EP1.5-4
Cross-Connection		
	CCS2.5/2	CCS4/2
	CCS2.5/3	CCS4/3
	CCS2.5/4	CCS4/4
	CCS2.5/10	CCS4/10



	ERPE2.5-T15 Width 5mm	ERPE4-T15 Width 6mm
Electrical Ratings		
Voltage / Current / Cross Section	-V~ / -A / 2.5mm ²	-V~ / -A / 4mm ²
VDE		
UL	-V~ / -A / AWG 26-12	-V~ / -A / AWG 26-10
ATEX	Yes	Yes
Connection Data		
Insulation Stripping Length / Torque	10mm / 0.4Nm	10mm / 0.5Nm
Solid Strand	0.5 - 4mm ²	0.5 - 6mm ²
Fine Strand, with Ferrule	0.5 - 2.5mm ²	0.5 - 4mm ²
AWG Conductor	26.....12	26.....10
End Bracket		
Thickness 8mm	 ES5	ES5
End Plate		
Polyamide 66 - Thickness 3mm	 EP1.5-4-GREEN	EP1.5-4-GREEN