




# ERT 3S Series

## Three Level Sensor Screw Clamp Terminals



ERT3S		Width 6mm
<b>Electrical Ratings</b>		
Voltage / Current / Cross Section	500V~ / 24A / 2.5mm <sup>2</sup>	
VDE		
UL/cUL	300V~ / 24A / AWG 24-12	
<b>Connection Data</b>		
Insulation Stripping Length / Torque	8mm / 0.4 - 0.6Nm	
Solid Strand	0.5 - 4mm <sup>2</sup>	
Fine Strand, with Ferrule	0.5 - 2.5mm <sup>2</sup>	
AWG Conductor	24.....12	
<b>End Bracket</b>		
For MR 32 & MR 35		ES1 ES3 ES4
<b>End Plate Partition</b>		
Polyamide 66 - Thickness 1.5mm		EPT3S
<b>Small Partition</b>		
		SP1
<b>Cross-Connection</b>		
		CC2.5/2T CC2.5/3T CC2.5/4T CC2.5/10T
<b>Test Plug-Soc</b>		
		TF2.3 TSK2.3
<b>Group Marking</b>		
		GM



ERT3SLDN	Width 6mm	ERT3SLDP	Width 6mm
-V~ / 24A / 2.5mm <sup>2</sup>		-V~ / 24A / 2.5mm <sup>2</sup>	
8mm / 0.4 - 0.6Nm		8mm / 0.4 - 0.6Nm	
0.5 - 4mm <sup>2</sup>		0.5 - 4mm <sup>2</sup>	
0.5 - 2.5mm <sup>2</sup>		0.5 - 2.5mm <sup>2</sup>	
24.....12		24.....12	
ES1		ES1	
ES3		ES3	
ES4		ES4	
EPT3S		EPT3	
SP1		SP1	
CC2.5/2T		CC2.5/2T	
CC2.5/3T		CC2.5/3T	
CC2.5/4T		CC2.5/4T	
CC2.5/10T		CC2.5/10T	
TF2		TF2	
TF3		TF3	
GM		GM	

