







PFD Series

Multi-Input / Output Push-Fit Terminals



PFD1.5C		Width 4.2mm
Electrical Ratings		
Voltage / Current / Cross Section	24VDC / 10A / 4mm ²	
UL		
Connection Data		
Insulation Stripping Length	10mm	
Solid Strand	0.5 - 6mm ²	
Fine Strand with Ferrule	0.5 - 4mm ²	
AWG Conductor	22.....10	
End Bracket		
	ES1	
	ES4 (screwless)	
End Plate		
Polyamide 66 - Thickness 1.0mm		EPPFD1.5C
Cross-Connection		
	CCS1.5/2	
	CCS1.5/3	
	CCS1.5/4	
	CCS1.5/10	
Test Plug		
	PFT	
Technical Data		
Max. Clamping Range	2.5mm ²	
Rated Impulse Voltage / Pollution Severity	8kV / 3	
Insulation Material Group / Gauge Pin Code (acc. IEC 60947-1)	1 / A3	
Protection Class / Protection Conductor Type	IP20 / -	



PFD2.5E	Width 5mm	PFD2.5C	Width 5mm	PFD4E	Width 6mm
800V~ / 24A / 2.5mm ²		800V~ / 24A / 2.5mm ²		800V~ / 32A / 4mm ²	
600V~ / 20A / AWG 22-12		600V~ / 20A / AWG 22-12		600V~ / 30A / AWG 22-10	
10mm		10mm		10mm	
0.5 - 4mm ²		0.5 - 4mm ²		0.5 - 6mm ²	
0.5 - 2.5mm ²		0.5 - 2.5mm ²		0.5 - 4mm ²	
22.....12		22.....12		22.....10	
ES1		ES1		ES1	
ES4 (screwless)		ES4 (screwless)		ES4 (screwless)	
EPPFD2.5E		EPPFD2.5C		EPPFD4E	
CCS2.5/2		CCS2.5/2		CCS4/2	
CCS2.5/3		CCS2.5/3		CCS4/3	
CCS2.5/4		CCS2.5/4		CCS4/4	
CCS2.5/10		CCS2.5/10		CCS4/10	
PFT		PFT		PFT	
4mm ²		4mm ²		6mm ²	
8kV / 3		8kV / 3		8kV / 3	
1 / A3		1 / A3		1 / A4	
IP20 / -		IP20 / -		IP20 / -	

