












SCT Series

Multi-Level Spring Clamp Terminals



SCT3		Width 5mm
Electrical Ratings		
Voltage / Current / Cross Section	500V~ / 24A / 2.5mm ²	
UL / cUL	600V~ / 20A / AWG 22-12	
Connection Data		
Insulation Stripping Length / Torque	10mm / ...	
Solid Strand	0.5 - 4mm ²	
Fine Strand, with Ferrule	0.5 - 2.5mm ²	
AWG Conductor	22.....12	
End Bracket		
	ES4 (screwless)	
End Plate / Partition		
Polyamide 66 - Thickness 1.2mm	 EPSCT3	
Cross-Connection		
	CCS2.5/2	
	CCS2.5/3	
	CCS2.5/4	
	CCS2.5/10	
Test Plug		
	TF2	
Group Marking		
	GM	



SCPT2E	Width 5mm	SCT3E	Width 5mm
500V~ / 24A / 2.5mm ²		500V~ / 24A / 2.5mm ²	
600V~ / 20A / AWG 22-12		600V~ / 20A / AWG 22-12	
10mm / ...		10mm / ...	
0.5 - 4mm ²		0.5 - 4mm ²	
0.5 - 2.5mm ²		0.5 - 2.5mm ²	
22.....12		22.....12	
ES4 (screwless)		ES4 (screwless)	
EPSCD2.5		EPSCD2.5	
CCS2.5/2		CCS2.5/2	
CCS2.5/3		CCS2.5/3	
CCS2.5/4		CCS2.5/4	
CCS2.5/10		CCS2.5/10	
TF2		TF2	
GM		GM	

